

**FEE: \$60.00 per heat**

**4-vehicle minimum per heat  
for full pay-out**

## Brooklin Spring Fair 2024

### Demolition Derby Rules for: **JUNK RUN – 2024**

#### Demolition Derby General Rules – 2024 JUNK RUN

The Demolition Derby will be held:

**SATURDAY, JUNE 1<sup>st</sup>, 2024** at the Brooklin Demo Arena in Brooklin at **6:15 P.M. SHARP!**

In the event that this Derby is cancelled, the Brooklin Spring Fair Board will not be liable. There is no rain date.

These rules replace all previously issued rules and are subject to change without notice.

**ALL DRIVERS MUST ATTEND DRIVERS' MEETING  
PRIOR TO ANY HEAT  
OR DRIVER WILL BE DISQUALIFIED**

#### 2024 JUNK RUN - Vehicle Prep Rules

##### Vehicles Allowed

1. Preparation of the vehicle must occur before the vehicle arrives at 'The Fairgrounds'. This includes painting of the frame repairs as outlined.
2. **RUNNING RISK:** Demolition derbies are hazardous and high-risk sports; therefore, anyone with a health condition, i.e. concussion, heart problems, or who is pregnant should not compete. You are competing at your own risk. Protect yourself: Work boots, sport equipment such as, neck brace, knee pads, shoulder pads, hip pads, etc are recommended. No bare exposed skin. All drivers must wear long pants/coveralls as well as long-sleeved shirts. No exceptions. Working seat belt and racing helmet are mandatory. Helmets must have chin straps. Goggles or face shields are recommended.  
\*\*\*No motocross style visors.\*\*\*
3. Cars previously run in derbies **MAY** be considered too badly damaged and unsafe, resulting in disqualification. Call or email with pictures first.
4. **As in all Brooklin Spring Fair classes, a vehicle ownership must be on hand in case of vehicle issues.**
5. Brooklin Spring Fair Demolition Derby Committee or promoter reserves the right to approve or reject any and all entries, drivers or pit persons.
6. It is highly recommended that each competitor carry their own liability insurance.
7. Drivers and mechanics are in the pit area at their own risk.

**NEW: Please note the change in rules for Vehicle Prep for trucks, straight stock and junk run**

**NEW:** BELT DRIVEN fans may be used as long as the hood is securely in place. No hood -- No belt driven fan. An electric fan may be used in place of the belt driven fan.

### Vehicle Prep

1. Any factory built 4- or 6-cylinder minivans, compact SUV, compact/light duty truck, AWD/4X4 vehicles allowed with one drive shaft removed.
2. No hearses, limousines or checker cabs. No half ton trucks. Check with Brooklin Spring Fair Demolition Derby Committee if your make and model is questionable.
3. Vehicles must have dependable brakes and must be working properly before entering the ring at all times. All boundaries must be observed.
4. Additional Safety regulations may be imposed, depending on track and conditions.
5. **The Demolition Derby Officials' decision is final when inspecting vehicles. Do not put yourself in a disqualification position by bending or ignoring rules.**
6. 4" x 4" **patches** to be a max ¼" thick
7. All **repairs** must be with stock style components. No reinforcing.
8. All **flammable material** must be removed from the cab area except the dash, driver's seat and seat belt. This includes carpeting, headliner, door panels and trim. All debris, including in the doors and trunk must be removed.
9. All **air bags** to be removed.
10. **Trailer hitches** and frame reinforcements must be removed.
11. **All glass**, windows, mirrors, trim, lights, antennas, ornaments, bezels, interior and exterior must be removed (including bulbs).
12. The **AC system** must be drained.
13. The **cooling system** must be flushed of antifreeze and replaced with water only. Radiator to be in its original position or removed. The over flow tube must be secured to direct the coolant to the ground. No additional protection except stock AC condenser. No reinforcements or guards. Stock type radiators only.
14. **\*\*\*New\*\*\*Belt driven fans** may be used as long as the hood is securely in place. **No hood, No belt driven fan.** An electric fan may be used in place of the belt driven fan.
15. **Driver's door** must be painted white, passenger optional (for ease of seeing the number).
16. A CSA approved **fire extinguisher**, with properly functioning gauge, (ABC) must be properly secured within reach of the driver.
17. One 12-volt **battery** must be properly secured to the front passenger floor board area in a box. This area must be clear of all fuel system parts. Once the inspection has been completed, this battery will be covered with a non-flammable material, shield to control possible splashes. One 12V battery only.
18. The **stock fuel tank** must be removed with all loose fuel lines and straps. It is to be replaced with a CSA approved, steel marine fuel tank, plastic approved fuel tank, custom fuel tank or racing fuel cell. The replacement fuel tank will be positioned in the rear seat area centered between the sides. It will be held

securely in place, no leaks, and will be covered with a non-flammable splash cover after the inspection. No movement will occur when inspected.

19. All **fuel lines** must have must have leak proof fittings with steel or approved fuel rubber lines (no clear lines). Lines must be inside the vehicle, if possible, secured and protected. For electric fuel systems a **RED** safety shut off switch, for the pump only, must be installed, on the roof or dash in the centre of the windshield opening for officials, safety purposes. The fuel pump must be isolated, and all components covered with a non-flammable material. Any leaks, at any time, will result in an immediate disqualification.
20. **Hoods** must remain open for inspection. A 12" hold must be cut in the centre of the hood. Hoods must be fastened down in a maximum of 8 places with treaded rod, seat belt material, wire, chain or bolted to the fender. **No welding**. Hood latches may be removed. Hoods or rad supports may be wired to the bumper in 4 locations.
21. Front rubber **body mounts** must be in place. These may be substituted with hockey pucks.
22. **Tailgates or trunks** can be wired chained or strapped closed in 8 locations max. 4 of these may be to the rear bumper max. The Trunk can be bent or creased only, **NOT the rear parcel shelf**. A maximum of 2 spots can be bolted with  $\frac{3}{4}$  threaded rod and flat washers no larger than 4 inches diameter or square to secure the trunk or tailgate. No folding of box sides or tailgates. Stock position.
23. NO Pre bending body modifications. No body shaping other than the trunk. Used cars do not apply to this rule.
24. Metal may be removed from the wheel openings for clearance. Front fenders and rear quarter panels may be bolted with 5,  $\frac{3}{8}$ " bolts maximum. No Body Creasing.
25. All **doors** must be fastened shut with chain, wire or seat belts straps in a maximum of 8 locations. The **driver's door only** may be welded in place with 3" x 3" plates. A 12" x 72" x  $\frac{1}{4}$  max plate may be used on the 2 front doors. The Driver's side is strongly recommended. No channel or angle iron allowed. These will be fastened on in 8 locations maximum with  $\frac{3}{4}$  " bolts and flat washers' maximum.
26. When building a **roll bar system** be careful not to reinforce the body structure through excessive material. A single roll bar may be used up each door frame inside and across the top. The upper roll bar may be bolted through the roof in 2 locations. It may be bolted or welded to the frame or rocker. If bolted 2,  $\frac{3}{4}$  bolts per side . 1 additional bar may be used behind the seat, welded or bolted to the vertical roll bars. The maximum size to be 4" tube, square or in diameter.
27. **Seat roll bar** not to extend past the back of the driver's seat. 1 bar can run down the inside of the door, from ash bar to seat bar. The bar over the roof cannot be attached to any other bar except the rear seat bar. 1 bar can run between the seats, from dash bar to seat bar to secure the shifter. Roll bar highly recommended.

28. The **front window** opening must have a minimum of 1 bar or chain from the front **cowl to the roof**, bolted or welded in the middle. An A or H configuration may also be used. This is to protect the driver only, not reinforce the structure or protect the distributor, if used. No rear window opening bars.
29. **A dash bar** may be used. This is to be a 4" tube, maximum, square or dia. It may be constructed from door frame to door frame but may not contact the firewall or distributor guard. No down bars. Dash bar highly recommended.
30. All openings in the **firewall** must be plugged with similar gauge metal. Large holes in the floor may be securely patched with a similar gauge metal. Do not reinforce. Driver's seat may be tied to the roof or door post to prevent breaking.
31. **BUMPERS:** Any factory-made bumper may be used. If you choose to use a piece of square tube as a bumper it can be no bigger than 4x4 or 3x5 and no thicker than 3/8. Tube bumpers cannot stick out more than 4" from the outside of the frame. If the ends are cut and bent on a 45-degree angle it can be as wide as the centre of the front tires. Tube bumpers must remain flat, you cannot build a point. You can do whatever you need to do within 6" from the back of the bumper. Rear bumpers must remain stock. Pick-up trucks only may have a max 3x3 tube welded between the rear frame rails so the rails do not become spears. Mandatory that front and rear bumpers have at least 2 spots of 9 wire, chain or seat belt holding bumper on. Mandatory that bumper covers be removed.
32. Car **differentials** only. Do not reinforce the frame or body. Control arms, trailing arms must be stock. No modifications allowed. No pinion brakes.
33. **Motor mounts** may be welded or chained. Aftermarket mounts may be used. Do not reinforce or add extras. 2 additional safety chains may be used between the engine and upper control arm area. **NO extra chains, wires, straps, etc. from the engine or transmission to the frame or body. No welded links.**
34. Tires: Tires PG rated. No triple side walls (tire flaps) on drive tires. Rims may have welded in centres only to change bolt pattern and not to strengthen the rim. No full centres. No valve stem protection.
35. Drive **tires** must be low aggression. **BREAKING OF THESE RULES MAY RESULT IN DISQUALIFICATION.** Tires must be air filled only. No spit rims, welding stem protectors, bead locks, fastening of tires to rims, studs. All wheel weights must be removed. Tires may be doubled. **NO triple sides on the drive wheels.**
36. Reinforcement of the frame or body while building guards is not allowed. Any style of engine guard will be fastened to the engine or transmission only. No transmission braces or aftermarket bellhousings. Engine cradles must be designed to protect the drivetrain only, not to be fastened to the body or frame.
37. **Suspensions** are to be **stock** in design. Rear coils may be wired or welded to the differential. No spring blocks or added helpers. Aftermarket or double rear arms allowed. Front suspension steering columns, steering linkage, drive shafts, control arms, ball joints, rear control arms may be exchanged. No reinforcing except the factory tie rod ends.
38. **Differential** gears may be welded.

39. Rusty or bent **frames** may be repaired using 4" x 4" patches max on 2 sides. All repairs must be painted in a bright colour. A maximum of 8 repair plates to be used with 3" between each repair. No frame modifications, tilting, hump plates, welding of seams, shortening, grafting, etc.
40. All rubber **body mounts and stock sized bolts** are to remain in place. Maximum flat washer size is 3". Four additional body mounts using ¾" threaded rod max are allowed. An additional 2 threaded rods, same size, are allowed for the rad cradle. 2 additional stock sized bolts may be added inside the driver's compartment on the floor. Threaded rods must not extend through the bottom portion of the frame.
- 

***Have a Question?***

***Contact***

***Dave Snowden - (905) 404-3235  
demoderby@brooklinspringfair.com***